

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 044 701 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

18.10.2000 Bulletin 2000/42

(51) Int. Cl.⁷: **A61M 16/04**

(21) Application number: 00302375.1

(22) Date of filing: 23.03.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 12.04.1999 GB 9908136

(71) Applicant:

Smiths Industries Public Limited Company
London, NW11 8DS (GB)

(72) Inventor: Neame, Simon

Broadstairs, Kent CT10 3DF (GB)

(74) Representative:

Flint, Jonathan McNeill et al
SMITHS INDUSTRIES PUBLIC LIMITED
COMPANY
765 Finchley Road
London NW11 8DS (GB)

(54) Obturators and tube assemblies

(57) An obturator 2 for a tracheostomy tube 1 has a strap 25 extending along its length between a nose 21 at its patient end 20 and a machine end 32 with clips 34 that fasten to a coupling 13 on the tube. The strap 25 has one web 26 extending along its entire length and a second web 27 extending orthogonally on one side of the first web to form a T shape section along the major part 28 of the strap towards its patient end. This makes the patient end 20 of the strap 25 relatively rigid whilst its machine end 32 is relatively flexible to enable the machine end to be twisted to release the engagement of the clips 34 and to enable the obturator 2 to be pulled out of the tube 1.




Fig.2.

EP 1 044 701 A2

Description

[0001] This invention relates to obturators of the kind for a curved medical tube, the obturator having a patient end shaped with a tapered nose arranged to protrude from the patient end of the tube and a machine end adapted to fasten with the machine end of the tube, the machine end of the obturator being releasable from engagement with the machine end of the tube by twisting relative to the tube.

[0002] The invention is more particularly concerned with obturators for use in tracheostomy tubes.

[0003] Tracheostomy tubes are often inserted with the aid of an obturator having a pointed end projecting from the patient end of the tracheostomy tube. The tip of the obturator helps separate tissue, enabling smooth entry of the tube. The obturator also helps stiffen the tube and prevents ingress of tissue into the tube, which could cause blockage. Examples of tracheostomy obturators are described in US4246897, US5222487, GB2224213, GB2316321 and GB2341102. Any displacement of the obturator from its correct position may make insertion of the tube more difficult and, by reducing the smoothness of the patient end of the assembly, may cause trauma to tissue around the stoma. After insertion, the obturator is pulled out of the machine end of the tube. GB 2316321 describes an obturator with a machine end that clips onto the coupling of the tracheostomy tube, the clip being released by twisting it relative to the tube. In this arrangement, the main body of the obturator is a strap of rectangular section so it is relatively flexible to enable twisting. This obturator works well with tracheostomy tubes that are relatively stiff but it does not provide optimal rigidity with more flexible tubes. Although the obturator could be made stiffer to give the desired rigidity for insertion of the tube, this makes it difficult to twist its clip to release engagement with the coupling of the tracheostomy tube.

[0004] It is an object of the present invention to provide an alternative obturator and tube assembly.

[0005] According to the present invention there is provided an obturator of the above-specified kind, characterised in that the obturator is substantially rigid along a major part of its length extending from the patient end, and that the obturator has a portion of its length adjacent its machine end that is relatively flexible to permit twisting.

[0006] The major part of the obturator preferably has two orthogonal webs. The obturator may comprise a first web extending along the length of the obturator from the patient end nose to the machine end and a second orthogonal web extending along only the more rigid part of the obturator. One web may be arranged to extend along substantially in contact with the outside curve of the tube. The obturator is preferably of T shape in section along its major part. The nose of the obturator may have a bore extending through it along its length. The obturator may be a single-piece moulding of a plas-

tics material. The machine end preferably has two resilient arms extending forwardly on opposite sides and adapted to engage the tube. The machine end of the obturator may have a vent hole therein. The obturator is preferably curved along most of its length with a curvature substantially the same as that of the tube.

[0007] A tracheostomy tube assembly including an obturator according to the present invention, will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a side elevation view of the assembly;

Figure 2 is a side elevation of the obturator;

Figure 3 is an elevation view of the obturator along the line III in Figure 2;

Figure 4 is an elevation view of the obturator along the line IV in Figure 2; and

Figure 5 is a cross-sectional view of the obturator along the line V-V of Figure 2; and

Figure 6 is a cross-sectional view of the obturator along the line VI-VI of Figure 2.

[0008] The assembly comprises a tracheostomy tube 1 and an obturator 2.

[0009] The tube 1 has a conventional shaft 10 of circular section, which is moulded with a curved shape and a constant radius of curvature along its length. The patient end 11 of the shaft 10 is cut square and tapered to be atraumatic. At its machine end, the shaft 10 is moulded integrally with a flange 12 by which the tube can be secured to the patient's neck. The machine end of the shaft 10 is also bonded to a coupling 13 having a female tapered bore 14 shaped to receive a male tapered coupling (not shown) connected to a patient ventilation or anaesthetic circuit. Alternatively, where the patient is breathing spontaneously, the coupling 13 is left open. Externally, the coupling 13 is of cylindrical shape apart from surface formations provided by two, short undercut lips 15 located diametrically opposite one another at the patient end of the coupling. The shaft 10 has an inflatable cuff 16 towards its patient end, for sealing with the inside of the trachea. Alternative tubes need not include such a cuff.

[0010] The obturator 2 is a single-piece, integral moulding of a stiff plastics material such as high density polyethylene. At its patient end 20, the obturator 2 has a bullet-shape nose 21, which is a close fit within the patient end 11 of the tube 1. The nose 21 has a tapered tip 22, which, in use, projects from the tube 1 so as to form a pointed continuation of the patient end of the shaft 10. A small diameter bore 23 extends along the nose 21 from its tip 22 to an opening 24 at its rear end.

[0011] Extending rearwardly from the nose 21 the

obturator has a curved strap 25 moulded to the curvature of the tube 1. Typically, the strap 25 is about 80mm long. The strap 25 comprises a web 26 of substantially rectangular section arranged to extend diametrically of the tube shaft 10 as a close sliding fit along its entire length. The strap 25 also has an additional web 27 extending along the major part of the length of the strap, typically along about 60mm, from the patient end. This additional web 27 extends radially and orthogonally of the first web 26 projecting from one side only towards the outside of its curve so that it substantially contacts the inner wall of the shaft 10 of the tube 1 on the outside of its curvature. The major part 28 of the strap 25 from its patient end therefore has a substantially T-shape in section, as shown in Figure 5, with just a shallow rib 29 along the side opposite the additional web 27 and is substantially rigid. The machine end 30 of the strap 25 has a substantially rectangular shape in section, as shown in Figure 6 apart from the rib 29 and a similar shallow rib 31 being a continuation of the additional web 27 and is, therefore, more flexible than the major part 28.

[0012] At its machine end 32, the obturator 2 has an enlarged, cruciform section formed by a vertical plate 132 and a horizontal plate 232. The machine end 32 has a tapered exterior, which is a close friction fit within the coupling 13 of the tube 1. A flange 33 extends radially at the machine end of the cruciform section 32 and provides a grip by which the obturator 2 can be inserted and removed from the tube 1. Two resilient arms 34 extend forwardly from the flange 33 on opposite sides of the obturator 2. The arms 34 are terminated at their patient end by surface formations in the form of inwardly-directed catches 35 formed by an inclined ramp 36 and a ledge 37. The dimensions of the arms 34 are such that, when the flange 33 abuts the machine end of the coupling 13, the arms extend along opposite sides of the coupling with the catches 35 engaging under the lips 15, thereby preventing the obturator 2 being removed from the tube. Two vent holes 38 are formed through the flange 33 in alignment with the corners between the cruciform section 32.

[0013] In use, the obturator 2 is pushed fully into the tube 1 so that the nose 21 projects from the patient end 11 of the tube and so that the catches 35 engage the lips 15 on the coupling 13, thereby fastening the machine end of the obturator with the machine end of the tube. The assembly is inserted into the patient in the usual way, the obturator 2 providing a tapered lead for the tube into the tracheostomy. The T-shape section along most of the length of the obturator 2 makes it relatively stiff so as to significantly increase the stiffness of the tracheostomy tube 1 and facilitate introduction. Rearward movement of the obturator 2 relative to the tube 1 is prevented by engagement of the catches 35 with the lips 15. Rearward movement of the nose 21 of the obturator 2 within the tube 1 is also resisted by contact of the additional web 27 with the wall of the tube.

The patient can breath through the assembly during insertion because of the bore 23 through the nose 21, the passage between the strap 25 and the inside of the tube, and the holes 38 in the flange 33. If desired, a guidewire (not shown) could be threaded through the bore 23 prior to insertion and the assembly slid into position along the guidewire. In order to prevent the rear end of the guidewire catching on the vertical plate 132 when the guidewire is inserted from the patient end of the obturator, the leading edge 133 of the vertical plate is tapered. When the assembly has been inserted to the correct location, the obturator 2 is removed by gripping the flange 33 and twisting it through about 20° so that the catches 35 come out of engagement with the lips 15 and can be pulled rearwardly along the outside of the coupling 13. The flange 33 can be twisted easily despite the stiffness of the patient end of the obturator 2 because the machine end 30 of the obturator is flexible to allow twisting. After removal of the obturator 2, the coupling 13 can be connected to a ventilation circuit or left open, in the usual way.

[0014] It will be appreciated that there are alternative twist-releasable arrangements that could be used to fasten the obturator with the tube. The invention could be used with tubes, other than tracheal tubes, where it is necessary to prevent displacement of an obturator relative to a tube.

Claims

1. An obturator (2) for a curved medical tube (1), the obturator (2) having a patient end (20) shaped with a tapered nose (21) arranged to protrude from the patient end (11) of the tube (1) and a machine end (32) adapted to fasten with the machine end (13) of the tube, the machine end (32) of the obturator (2) being releasable from engagement with the machine end of the tube by twisting relative to the tube, characterised in that the obturator (2) is substantially rigid along a major part (28) of its length extending from the patient end (20), and that the obturator has a portion (30) of its length adjacent its machine end (32) that is relatively flexible to permit twisting.
2. An obturator according to Claim 1, characterised in that the major part (28) of the obturator (2) has two orthogonal webs (26 and 27).
3. An obturator according to Claim 2, characterised in that the obturator (2) comprises a first web (26) extending along the length of the obturator from the patient end nose (21) to the machine end (32) and a second orthogonal web (27) extending along only the more rigid part of the obturator.
4. An obturator according to Claim 2 or 3, characterised in that one web (27) is arranged to extend

along substantially in contact with the outside curve of the tube (10, 1).

5. An obturator according to any one of the preceding claims, characterised in that the obturator (2) is of T shape in section along its major part (28). 5
6. An obturator according to any one of the preceding claims, characterised in that the nose (21) of the obturator (2) has a bore (23) extending through it along its length. 10
7. An obturator according to any one of the preceding claims, characterised in that the obturator (2) is a single-piece moulding of a plastics material. 15
8. An obturator according to any one of the preceding claims, characterised in that the machine end (32) has two resilient arms (34) extending forwardly on opposite sides and adapted to engage the tube (13, 1). 20
9. An obturator according to any one of the preceding claims, characterised in that the machine end (32) of the obturator (2) has a vent hole (38) therein. 25
10. An obturator according to any one of the preceding claims, characterised in that the obturator is curved along most of its length with a curvature substantially the same as that of the tube. 30

35

40

45

50

55




Fig.1.




Fig.2.

Fig.3.




Fig.4.




Fig.5.





Fig.6.





(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
11.07.2001 Bulletin 2001/28

(51) Int Cl.7: **A61M 16/04**

(43) Date of publication A2:
18.10.2000 Bulletin 2000/42

(21) Application number: **00302375.1**

(22) Date of filing: **23.03.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Neame, Simon**
Broadstairs, Kent CT10 3DF (GB)

(74) Representative: **Flint, Jonathan McNeill et al**
SMITHS INDUSTRIES PUBLIC LIMITED
COMPANY
765 Finchley Road
London NW11 8DS (GB)

(30) Priority: **12.04.1999 GB 9908136**

(71) Applicant: **Smiths Industries Public Limited**
Company
London, NW11 8DS (GB)

(54) **Obturator and tube assemblies**

(57) An obturator 2 for a tracheostomy tube 1 has a strap 25 extending along its length between a nose 21 at its patient end 20 and a machine end 32 with clips 34 that fasten to a coupling 13 on the tube. The strap 25 has one web 26 extending along its entire length and a second web 27 extending orthogonally on one side of

the first web to form a T shape section along the major part 28 of the strap towards its patient end. This makes the patient end 20 of the strap 25 relatively rigid whilst its machine end 32 is relatively flexible to enable the machine end to be twisted to release the engagement of the clips 34 and to enable the obturator 2 to be pulled out of the tube 1.




Fig.2.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 2375

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
D,X	GB 2 316 321 A (SMITHS INDUSTRIES LTD) 25 February 1998 (1998-02-25) * page 4, paragraph 2 - page 5, paragraph 2; figure 2 *	1,6-10	A61M16/04
A	---	4	
A	EP 0 371 752 A (SHETTY DEVI CARDIOTHORACIC UNI) 6 June 1990 (1990-06-06) * column 3, line 8 - line 35 * * figures 2,3 *	1,2,5,7	
A	---		
A	GB 2 310 605 A (SMITHS INDUSTRIES PLC) 3 September 1997 (1997-09-03) * page 3, paragraph 2 - paragraph 3; figures *	1,6,7,9	
D,A	---		
	US 5 222 487 A (CARR IAN R ET AL) 29 June 1993 (1993-06-29) * column 4, line 36 - line 54 * * figures 1,4,7 *	2-5,7	

			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 May 2001	Examiner Lakkis, A
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document	

EPO FORM 1503 03/02 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 2375

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-05-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2316321 A	25-02-1998	AU 725975 B	26-10-2000
		AU 3414197 A	26-02-1998
		EP 0824928 A	25-02-1998
		JP 10076010 A	24-03-1998
		US 5928198 A	27-07-1999
EP 0371752 A	06-06-1990	NONE	
GB 2310605 A	03-09-1997	NONE	
US 5222487 A	29-06-1993	US 5042475 A	27-08-1991
		AU 659375 B	11-05-1995
		AU 2268692 A	25-01-1993
		CA 2111861 A,C	07-01-1993
		DE 69227110 D	29-10-1998
		DE 69227110 T	15-04-1999
		EP 0590084 A	06-04-1994
		JP 2916261 B	05-07-1999
		JP 7500022 T	05-01-1995
		AU 620152 B	13-02-1992
		AU 4230789 A	05-04-1990
		CA 1313101 A	26-01-1993
		DE 3932598 A	05-04-1990
		FR 2637187 A	06-04-1990
		GB 2224213 A,B	02-05-1990
		IL 91777 A	13-05-1993
		JP 1849428 C	07-06-1994
		JP 2174858 A	06-07-1990
		JP 5065199 B	17-09-1993
		SE 502532 C	06-11-1995
		SE 8903146 A	31-03-1990
		WO 9300124 A	07-01-1993

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82